

## CLAIMS

1. A light source device comprising: an arc tube having  
a pair of main electrodes arranged on one electrode axis;  
5 and a reflector for reflecting an outgoing light emitted from  
the arc tube, the electrode axis of the main electrodes being  
arranged to cross a light axis of the outgoing light,  
wherein the reflector is formed of a first reflector portion  
having a spherical surface centered at a light generation  
10 point of the arc tube and a second reflector portion having  
a curved surface different from the first reflector portion,  
and

a condenser that condenses the outgoing light emitted  
from the arc tube to other than the second reflector portion  
15 so as to illuminate the condensed outgoing light in a  
predetermined direction or to a predetermined area is  
provided.

2. The light source device according to Claim 1 wherein  
20 the second reflector portion is formed with an ellipsoid.

3. The light source device according to Claim 1 wherein  
the second reflector portion is formed with a hyperboloid.

4. The light source device according to Claim 1 wherein  
25

the second reflector portion is formed with a spherical surface having a curvature different from the spherical surface of the first reflector portion.

5        5.     The light source device according to any one of Claims 1 to 4, further comprising a luminance equalization means for equalizing a surface luminance of the light beams by shaping the outgoing light emitted from the arc tube into a designated pattern and by mixing by multiple reflection.

10

6.     The light source device according to any one of Claims 1 to 4, further comprising a luminance equalization means for equalizing a surface luminance of the light beams by shaping the outgoing light emitted from a light source into a designated pattern and by mixing by multiple reflection.

15

7.     The light source device according to Claim 5 or 6, wherein the reflector and the luminance equalization means are integrally formed.

20

8.     The light source device according to any one of Claims 1 to 7, wherein sealed portions that seal the main electrodes are formed on both sides of the light generation point of the arc tube, and heat radiation members are arranged between the sealed portions and the reflector.

25

9. The light source device according to any one of Claims 1 to 8, wherein the reflector has a separable structure such that it can be separated along a plane perpendicular to the optical axis.

5

10. The light source device according to any one of Claims 1 to 9, wherein the reflector has a separable structure such that it can be separated along a plane parallel to the optical axis.

10

11. A video display apparatus in which the light source device according to any one of Claims 1 to 10 is used.